



DESIGN STANDARD/设计标准		JIS F 7310-1996
TEST/检验		JIS F 7400-1996
HYDRAULIC INSPECTION/压力试验		
TEST PRESSURE / 试验压力 Mpa	DODY / 强度	3.3
	SEAT / 密封	2.42
MEDIUM: WATER, AIR, GAS, OIL, STEAM		
TEMPERATURE: ≤205°C		

DN	d	L	D	C	NO.	h	t	H	D2
50	50	120	155	120	8	19	20	255	160
65	65	130	175	140	8	19	22	270	200
80	80	150	200	160	8	23	24	295	224
100	100	170	225	185	8	23	26	330	250
125	125	200	270	225	8	25	26	390	315
150	150	225	305	260	12	25	28	435	355
200	200	250	350	305	12	25	30	540	450

8	手轮	HT200		HANDWHEEL	FC200	
7	垫片	非石棉		GASKET	non-asbestos	
6	压盖	ZCuSn5Pb5Zn5		packing gland	BC6	
5	阀杆	HP59-1	1Cr12	STEM	C3771BD OR BE	SUS 403
4	阀座	ZCuSn5Pb5Zn5	ZG2Cr13	VALVE SEAT	BC6	SCS2
3	阀盘	ZCuSn5Pb5Zn5	ZG2Cr13	DISC	BC6	SCS2
2	阀盖	HT200		BONNET	FC200	
1	阀体	HT200		BODY	FC200	
序号	零件名称	CLASS B	CLASS S	NAME OF PART	CLASS B	CLASS S
		材料			MATERIAL	
铸铁角式截止阀 16K				Cast iron 16K Angle valves		



**Flowspec Industrial Limited**

**Luokai Industrial Co., Ltd.**