

DESIGN STANDARD/设计标准		JIS F 7319-1996
TEST/检验		JIS F 7400-1996
HYDRAULIC INSPECTION/压力试验		
TEST PRESSURE / 试验压力 Mpa	DODY / 强度	2.1
	SEAT / 密封	1.54
MEDIUM: WATER, AIR, GAS, OIL, STEAM		
TEMPERATURE: ≤300°C		


FLOWSPEC LUOKAI INDUSTRIAL CO., LTD.

DN	d	L	D	C	NO.	h	t	H	D2
50	50	220	155	120	4	19	16	270	160
65	65	270	175	140	4	19	18	300	200
80	80	300	185	150	2	19	18	310	200
100	100	350	210	175	2	19	18	355	250
125	125	420	250	210	2	23	20	415	280
150	150	490	280	240	2	23	22	470	315
200	200	570	330	290	12	23	22	565	355

8	手轮	HT200	HANDWHEEL	FC200
7	垫片	非石棉	GASKET	non-asbestos
6	压盖	ZCuSn5Pb5Zn5	packing gland	BC6
5	阀杆	1Cr12	STEM	SUS 403
4	阀座	ZG2Cr13	VALVE SEAT	SCS2
3	阀盘	ZG2Cr13	DISC	SCS2
2	阀盖	ZG230-460	BONNET	SC480
1	阀体	ZG230-460	BODY	SC480

序号	零件名称	材料	NAME OF PART	MATERIAL
----	------	----	--------------	----------

铸钢球形截止阀 10K Cast Steel 10K globe valves

	Flowspec Industrial Limited
	Luokai Industrial Co., Ltd.